

800-558-5066 f 920-983-9291

www.npsspillcontrol.com

SAFETY DATA SHEET

SECTION I: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Universal Sorbents
PRODUCT FORM: Fabric
CHEMICAL FAMILY: Polyolefin
PRODUCT DESCRIPTION: Pads, socks, booms, pillows and rolls designed to absorb all types of liquids, water and oil based. Not recommended for aggressive fluids. Color coded for safety in gray, yellow and green.

MANUFACTURER'S NAME: NPS Spill Control, LLC

MANUFACTURING LOCATION:

NPS Spill Control, LLC 8921 S. 187th Street Kent, WA 98031

NPS Spill Control, LLC 3250 Commerce Street Port Arthur, TX 77642

www.npsspillcontrol.com

CUSTOMER SERVICE: 1-888-490-2222 **TECHNICAL INFORMATION:** 1-425-656-4440 **EMERGENCY:** CHEMTREC 800-424-9300

SECTION II: HAZARD(S) IDENTIFICATION

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATING:

HEALTH: 0 FLAMMABILITY: 1 REACTIVITY: 0

*Not considered a hazardous material at temperatures below melting point. Not considered a controlled substance or a carcinogen.

POTENTIAL HEALTH EFFECTS:

EYE CONTACT: May cause irritation **INGESTION:** No hazard in normal use of product **SKIN CONTACT:** No hazard in normal use of product **CHRONIC:** Not applicable

SECTION III: COMPOSITION/INFORMATION ON INGREDIENTS



800-558-5066 f 920-983-9291

www.npsspillcontrol.com

INGREDIENTS	PERCENT	CAS NUMBER	OSHA PEL	ACGIH TLV
Polypropylene	98.3%	9003-07-0	N/A	N/A
Surfactant	1.4%	N/A	N/A	N/A
Color dye	0.3%	N/A	N/A	N/A

SECTION IV: FIRST AID MEASURES

EYE CONTACT: Use eyewash, or flush with water for 15 minutes consult physician if accompanied by pain or irritation.

SKIN CONTACT:	N/A
INHALATION:	N/A
INGESTION:	N/A

SECTION V: FIRE FIGHTING MEASURES

FLASH POINT:	329° C (625° F)			
AUTO IGNITION:	357° C (675° F)			
FLAMMABLE LIMITS:	N/A			
FIRE EXTINGUISHING MEDIA:	Water, Foam, CO2,			
Dry Chemical				
SPECIAL FIRE FIGHTING PROCEDURES:	Standard procedures			
for Class A fires				
UNUSUAL FIRE AND EXPLOSION HAZARDS: Some carbon monoxide for				
	oxvgen-lean conditions. M			

5: Some carbon monoxide formation is possible under oxygen-lean conditions. Matting will not support combustion. Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the

chemical absorbed before proceeding

SECTION VI: ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: If material is unused, sweep or pick up and dispose of as a non-hazardous material.

SECTION VII: HANDLING AND STORAGE

Store in dry area. Do not store near open flame, high heat, strong oxidants, or halogenated hydrocarbons. Polypropylene, when heated, becomes very sticky and will burn. Use self-contained air masks to enter smoky area in the event of fire. Adequate ventilation is required to remove decomposition products when temperature exceeds melting point. Avoid contact with melted product.



3303 Spirit Way Green Bay, WI 54304 800-558-5066 *f* 920-983-9291

www.npsspillcontrol.com

Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

SECTION VIII: EXPOSURE CONTROLS/ PERSONAL PROTECTION

ENGINEERING PROTECTION: None Required

RESPIRATORY PROTECTION: None Required **VENTILATION**: None Required **PROTECTIVE GLOVES:** Not required. However, use of cloth, canvas or leather gloves is a good industrial practice

EYE PROTECTION: Safety glasses with side shields are recommended as a good practice for industrial safety.

OTHER PROTECTIVE EQUIPMENT: None Required

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: SPECIFIC GRAVITY: BOILING POINT (C):	Gray, Yellow or Green & virtually odor free 0.88 – 0.92 Not Applicable
MELTING POINT (C):	>160° C (320° F)
FLASH POINT(C):	625 ° C (1157° F)
SOLUBILITY IN WATER:	Insoluble
PERCENT VOLATILE BY VOLUME:	N/A
EVAPORATION RATE:	N/A
VAPOR PRESSURE (mm Hg):	N/A
VAPOR DENSITY (Air = 1):	N/A

SECTION X: STABILITY AND REACTIVITY

GENERAL: This is stable material **CONDITIONS OF REACTIVITY:** Hazardous reactions will not occur under normal conditions **CONDITIONS TO AVOID:** Strong oxidizing agents may degrade product over an extended period of time **HAZARDOUS DECOMPOSITION:** When heated, it may emit toxic fumes **HAZARDOUS POLYMERIZATION:** Will not occur

SECTION XI: TOXICOLOGICAL INFORMATION

LD50: Not Available LC50: Not Available CARCINOGENICITY: IARC: Not established National Toxicology Program: Not Established OSHA: Not established

800-558-5066 f 920-983-9291

www.npsspillcontrol.com



California Prop 65: No listed ingredient **REPRODUCTION TOXICITY:** Not available **TERATOGENICITY:** Not available **MUTAGENICITY:** Not available **SYNERGISTIC PRODUCTS:** Not available **IRRITANCY OF PRODUCT:** See section II **SENSITIZATION TO PRODUCT:** Not available

SECTION XII: ECOLOGICAL INFORMATION

No data available

SECTION XIII: DISPOSAL CONSIDERATIONS

Disposal must be done in accordance with local, state and federal regulations based on chemicals adsorbed by products. Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous.

Always refer to the MSDS for the chemical absorbed before proceeding

SECTION XIV: TRANSPORT INFORMATION

DOT CLASSIFICATION: Non Hazardous

SECTION XV: REGULATORY INFORMATION

DEPARTMENT OF TRANSPORTATION CLASS: Not Regulated DEPARTMENT OF TRANSPORTATION IDENTIFICATION NUMBER: None TSCA: This product is listed in the TSCA Inventory CERCLA: This product is not subject to reporting OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200: Not listed CERCLA: This product is not subject to reporting SARA TITLE III: Not hazardous, No reportable ingredients

SECTION XVI: OTHER INFORMATION

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

REASON FOR ISSUE: This document has been changed to comply with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 **DATE ISSUED:** March 26, 2004 **REVIEWED:** (With changes) April 23, 2015 **PREPARED BY:** NPS Spill Control, LLC.



800-558-5066 f 920-983-9291

www.npsspillcontrol.com

