





Headband, Passive

left/RIGHT Passive Hearing Protection

MSA left/RIGHT passive headband hearing products offer three levels of NRR values ranging from 21 to 28 dBA, making it simple to match the attenuation of the earmuff with the noise exposure of the worker.

- Classification:** Headband, Passive
- Markets:** General industry, manufacturing, repair and maintenance, construction, OGP, forestry, shipbuilding, mining
- Applications:** Heavy mechanical industries, compression rooms, airports (HIGH)
Utilities, construction, general industry (MEDIUM)
Food manufacturing, automotive, light industry (LOW)
- Standards:** Meets ANSI S3.19-1974 and CSA Class A Standards

	Product Name	Part No.	NRR	Product Features
	left/RIGHT (HIGH)	10087399	28 dBA	<ul style="list-style-type: none"> • For use in high-noise environments, such as paper mills, foundries, mines and airports • Cups are sized and shaped to provide space for most ear sizes
	left/RIGHT (MEDIUM)	10087426	25 dBA	<ul style="list-style-type: none"> • For use in medium-noise environments, such as oil, gas and petrochemical, forestry and agriculture • Cups are sized and shaped to provide space for most ear sizes
	left/RIGHT (LOW)	10087436	21 dBA	<ul style="list-style-type: none"> • For use in low-noise environments, such pharmaceuticals and outside maintenance, where overprotection is a concern

	Product Name	Part No.	Product Features
	left/RIGHT (HIGH) Hygiene Kit	10092880	<ul style="list-style-type: none"> • Cushions and inserts • Works with left/RIGHT passive helmet-mounted or headband products
	left/RIGHT (MEDIUM) Hygiene Kit	10092879	
	left/RIGHT (LOW) Hygiene Kit	10092878	