



# Product Information Sheet

## WHEELED CARBON DIOXIDE



Our residue-free wheeled Carbon Dioxide units are designed for one-man operation and are constructed with spun steel cylinders and plated brass valve assemblies. DOT approved cylinders, rugged frames and solid rubber tires are key features of these UL approved units.

Suitable for use on Class B and Class C fires.

**TYPICAL USES:** For protecting sensitive electronic equipment in refineries, shipboard, laboratories, construction sites, chemical plants and manufacturing facilities.



Model	C-50-SE	C-100-SE
<b>PART #</b>	35050	35100
<b>AGENT CAPACITY</b>	50 lb. (22.68 kg)	100 lb. (45.36 kg)
<b>UL RATING</b>	20-B:C	20-B:C
<b>DISCHARGE TIME</b>	40 sec	80 sec
<b>RANGE</b>	15 ft. (4.6 m)	15 ft. (4.6 m)
<b>SHIP WEIGHT</b>	250 lb. (113.4 kg)	390 lb. (176.9 kg)
<b>UNIT HEIGHT x WIDTH x DEPTH</b>	60" x 31" x 21" (152.4 x 76.2 x 53.3 cm)	65" x 30" x 21" (165.1 x 76.2 x 53.3 cm)
<b>UNIT DIAMETER</b>	3.375 in (8.6 cm)	3.375 in (8.6 cm)
<b>HOSE DIAMETER &amp; LENGTH</b>	.75 in x 25 ft. (1.9 cm x 7.6 cm)	1 in x 40 ft. (2.5 cm x 12.2 cm)

