



**COMBAT®** has an extensive variety of portable extinguishers ranging from ABC Dry Powder, Halotron I, Carbon Dioxide, Foam and Water Fire Extinguishers. Most of our products are approved to BS-EN3 by LPCB (UK). They are also certified to CE & MED application.



## ABC DRY POWDER STORED PRESSURE EXTINGUISHER (Blue Colour Band)

- Approved to BS EN3/SS232
- Top Quality Fire Extinguisher
- Effective Suppression for Class A, B, C & E Fires
- Non-Conductive of Electricity
- Fast Knock Out Effect
- Signal Red (RAL3000) Epoxy Polyester Powder Coating
- Widely Used in Commercial Buildings, Industrial Plants, Workshops etc.



## FOAM STORED PRESSURE EXTINGUISHER (Cream Colour Band)

- Approved to BS EN3/SS232
- Effective Suppression for Class A & B Fires
- Not Applicable for fires involving live electrical equipment
- Signal Red (RAL3000) Epoxy Polyester Powder Coating

## WATER STORED PRESSURE EXTINGUISHER (Red Colour Band)

- Approved to BS EN3/SS232
- Effective Suppression for Class A Fires
- Not Applicable for fires involving live electrical equipment
- Signal Red (RAL3000) Epoxy Polyester Powder Coating

Extinguishing Model	C-1ASE	C-2ASE	C-3ASE	C-4ASE	C-6ASE	C-9ASE	C-9PKSE	C-6FSE	C-9FSE	C-6WSE	C-9WSE
Capacity	1.0kg	2.0kg	3.0kg	4.0kg	6.0kg	9.0kg	9.0kg	6.0Ltr	9.0Ltr	6.0Ltr	9.0Ltr
Extinguishing Medium	ABC 40% Dry Chemical Powder						Purple K	AFFF Foam & Additive		Water & Additive	
Propellant Type	Nitrogen										
Fire Rating	5A/55B	13A/55B	13A/55B	21A/144B	34A/233B	43A/233B	144B	8A/113B	34A/233B	8A	13A
Class of Fire	A,B,C & Electrical						B,C & Electrical	A,B		A	
Test Pressure							23 kgf/cm <sup>2</sup>				
Max Working Pressure							14 kgf/cm <sup>2</sup>				
Overall Height (mm)	313	445	460	473	503	610	610	503	610	503	503
Diameter (mm)	85	98	115	139	181	181	181	181	181	181	181
Width (mm)	90	100	110	185	232	232	232	232	232	232	232
Empty Weight (kg)	1.01	1.60	1.97	2.43	3.39	4.01	4.01	4.06	4.36	3.76	4.43
Full Weight (kg)	2.01	3.60	4.97	6.43	9.39	13.01	13.01	10.04	13.36	9.76	13.43
Min. Discharge Time (Sec)	6.1	6.9	11.7	15	16	17	13.3	40	60	40	83
Min. Discharge Range (M)	3	3	3	5	5	7	7	4	4	4	6
Operating Temperature Range	-20°C to +60°C						+5°C to +60°C				
Safe Operating Distance	2 meters										
Cylinder Material	Cold Roll Steel Sheet										
LPCB (UK)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
CE Mark *	✓	✓	-	✓	✓	✓	-	-	✓	-	✓
Wheel Mark	-	-	-	✓	✓	✓	-	-	✓	-	✓

TECHNICAL SPECIFICATION



The company reserves the right to change the specification without prior notice.

LINGJACK ENGINEERING WORKS PTE LTD

Contact 65 6759 4163 • Facsimile 65 6758 7513 • Website www.combat.com.sg • Email combat@lingjack.com