



Announcing the latest addition to a stellar line of fire extinguishers ...

# The Offshore Line



Made for the harshest of environments, the Offshore product line of extinguishers comes with features specifically designed to keep them on watch and in shipshape operating condition.


**Offshore extinguishers ... the perfect storm of performance, durability, and value.**

**Key Features:**

- Rugged steel cylinders/frames, stainless steel operating levers, and plated brass valves.
- The agent cylinders and the wheeled model frames have a galvanizing compound undercoat, baked-on enamel top coat, and protective clear coat finish to prevent corrosion and fading from exposure to sun and sea – passes 3000 hour salt spray test.
- All nameplate labels have UV resistant lamination to prevent sun damage.
- Plated brass guard around the pressure gauge and a vinyl ring on the cylinder bottom of the hand portable extinguishers prevent the kind of damage that would deep-six any other fire extinguisher.
- Meets DOT and Transport Canada requirements.
- UL and ULC Listed with the same high fire ratings as Buckeye's standard models.
- All hand portable extinguishers are USCG Approved with noted marine bracket.
- Trilingual nameplate labels – English, Spanish, and French



# Offshore Wheeled Fire Extinguisher Specifications



SP = Stored Pressure  
PT = Pressure Transfer  
RG = Regulated Pressure

**Operating Temperature**  
Dry Chemical Models: -65°F to 120°F  
Halotron Models: -40°F to 120°F

**Operating Pressure**  
Hand Portable: 195 psi  
Dry Chemical Wheeled: 240 psi  
Halotron Wheeled: 150 psi

Model	Part No.	Agent Type	Agent Capacity	UL/ULC Rating	Discharge Time	Discharge Range	Unit Wt. (lbs.)	Hose Length	Wheel Type	Wheel Dims. Dia./Width
OS A-50-SP	30360	ABC	50 lbs.	10A:160B:C	36 sec.	25-35 ft.	154	25 ft.	Rubber	12.3 x 3.5 ins.
OS A-150-SP	31360	ABC	125 lbs.	30A:240B:C	47 sec.	30-40 ft.	300	50 ft.	Rubber	16 x 4 ins.
OS A-150-PT	31490	ABC	125 lbs.	30A:240B:C	43 sec.	30-40 ft.	325	50 ft.	Rubber	16 x 4 ins.
OS A-150-RG	31460	ABC	125 lbs.	30A:240B:C	44 sec.	30-40 ft.	387	50 ft.	Rubber	16 x 4 ins.
OS A-150-RG	31470	ABC	125 lbs.	30A:240B:C	44 sec.	30-40 ft.	422	50 ft.	Steel	36 x 2.5 ins.
OS A-150-RG	31480	ABC	125 lbs.	30A:240B:C	44 sec.	30-40 ft.	434	50 ft.	Steel Wheel Rubber Tread	36 x 2.5 ins.
OS A-350-PT	32180	ABC	300 lbs.	30A:320B:C	53 sec.	30-40 ft.	657	50 ft.	Steel	36 x 6 ins.
OS A-350-PT	32190	ABC	300 lbs.	30A:320B:C	53 sec.	30-40 ft.	683	50 ft.	Steel Wheel Rubber Tread	36 x 6 ins.
OS A-350-RG	32160	ABC	300 lbs.	30A:320B:C	52 sec.	30-40 ft.	780	50 ft.	Steel	36 x 6 ins.
OS A-350-RG	32170	ABC	300 lbs.	30A:320B:C	52 sec.	30-40 ft.	806	50 ft.	Steel Wheel Rubber Tread	36 x 6 ins.
OS K-50-SP	30760	PK	50 lbs.	160B:C	36 sec.	25-35 ft.	154	25 ft.	Rubber	12.3 x 3.5 ins.
OS K-150-SP	31760	PK	125 lbs.	320B:C	54 sec.	30-40 ft.	300	50 ft.	Rubber	16 x 4 ins.
OS K-150-PT	31590	PK	125 lbs.	320B:C	54 sec.	30-40 ft.	325	50 ft.	Rubber	16 x 4 ins.
OS K-150-RG	31560	PK	125 lbs.	320B:C	55 sec.	30-40 ft.	387	50 ft.	Rubber	16 x 4 ins.
OS K-150-RG	31570	PK	125 lbs.	320B:C	55 sec.	30-40 ft.	422	50 ft.	Steel	36 x 2.5 ins.
OS K-150-RG	31580	PK	125 lbs.	320B:C	55 sec.	30-40 ft.	434	50 ft.	Steel Wheel Rubber Tread	36 x 2.5 ins.
OS K-350-PT	32380	PK	300 lbs.	320B:C	62 sec.	30-40 ft.	657	50 ft.	Steel	36 x 6 ins.
OS K-350-PT	32390	PK	300 lbs.	320B:C	62 sec.	30-40 ft.	683	50 ft.	Steel Wheel Rubber Tread	36 x 6 ins.
OS K-350-RG	32360	PK	300 lbs.	320B:C	57 sec.	30-40 ft.	780	50 ft.	Steel	36 x 6 ins.
OS K-350-RG	32370	PK	300 lbs.	320B:C	57 sec.	30-40 ft.	806	50 ft.	Steel Wheel Rubber Tread	36 x 6 ins.
OS W-65	76501	Halotron	65 lbs.	4A:60B:C	20 sec.	15-25 ft.	252	25 ft.	Rubber	16 x 4 ins.
OS W-150	71501	Halotron	150 lbs.	10A:120B:C	30 sec.	23-36 ft.	396	50 ft.	Rubber	16 x 4 ins.

## USCG APPROVED MODELS – 30360, 31360, 30760, and 31760

# Offshore Hand Portable Fire Extinguisher Specifications

Model	Part No.	Agent Type	Agent Capacity	UL/ULC Rating	Discharge Time	Discharge Range	Shipping Wt. (lbs.)
OS 5 ABC	10960	ABC	5 lbs.	3A:40B:C	14 sec.	12-18 ft.	10 lbs.
OS 10 ABC	11360	ABC	10 lbs.	4A:80B:C	22 sec.	15-21 ft.	18.25 lbs.
OS 20 ABC	12360	ABC	20 lbs.	10A:120B:C	27 sec.	15-21 ft.	33.5 lbs.
OS 30 ABC	13360	ABC	30 lbs.	10A:160B:C	32 sec.	25-30 ft.	52.25 lbs.
OS 5 PK	11260	PK	5 lbs.	20B:C	9 sec.	12-18 ft.	10 lbs.
OS 10 PK	11760	PK	10 lbs.	80B:C	22 sec.	15-21 ft.	18.25 lbs.
OS 20 PK	12760	PK	20 lbs.	120B:C	27 sec.	15-21 ft.	33.5 lbs.
OS 30 PK	13760	PK	30 lbs.	160B:C	32 sec.	25-30 ft.	52.25 lbs.

All models are USCG Approved for marine vessel use when used in conjunction with the bracket specified on the label