



Manufacturer of the
World's finest fire
safety products.



**Dry Chemical
Wheeled Units**

WHEELED DRY CHEMICAL



Our comprehensive line of wheeled dry chemical extinguishers is available in three types and designed to meet the majority of large extinguishing needs.


Designed for one man operation these units are easily transportable through doorways and over rough terrain.

All models are rechargeable and meet relevant UL & DOT requirements. Selected models have US Coast Guard Approvals.

Stationary models are also available.

TYPICAL USES: Offshore rigs, ship docks, refineries, chemical plants, aircraft ramps, remote construction sites, large laboratories, processing plants, storage and loading areas. Not for use on sensitive electronic equipment.

Dry chemical wheeled units are available for Class A, Class B and Class C fires.



WHEELED DRY CHEMICAL - PRODUCT SPECIFICATION

| MODEL | TYPE | PART NUMBER | AGENT CAPACITY | UL RATING | DISCHARGE TIME | DISCHARGE RANGE | SHIP WEIGHT |
|----------|-----------------------|-------------|-------------------|--------------|----------------|------------------------|------------------|
| A-50-SP | ABC Dry Chemical | 30010 | 50 lb. (22.7 kg) | 10-A:160-B:C | 35 sec | 25-35 ft. (7.6-10.7 m) | 193 lb. (88 kg) |
| A-150-SP | ABC Dry Chemical | 30110 | 125 lb. (56.7 kg) | 30-A:240-B:C | 47 sec | 30-40 ft. (9.1-12.2 m) | 343 lb. (156 kg) |
| A-150-RG | ABC Dry Chemical | 31120 | 125 lb. (56.7 kg) | 30-A:240-B:C | 43 sec | 30-40 ft. (9.1-12.2 m) | 413 lb. (188 kg) |
| A-150-RG | ABC Dry Chemical | 31140 | 125 lb. (56.7 kg) | 30-A:240-B:C | 43 sec | 30-40 ft. (9.1-12.2 m) | 448 lb. (204 kg) |
| A-150-RG | ABC Dry Chemical | 31150 | 125 lb. (56.7 kg) | 30-A:240-B:C | 43 sec | 30-40 ft. (9.1-12.2 m) | 448 lb. (204 kg) |
| A-150-PT | ABC Dry Chemical | 31110 | 125 lb. (56.7 kg) | 30-A:240-B:C | 45 sec | 30-40 ft. (9.1-12.2 m) | 345 lb. (147 kg) |
| A-350-RG | ABC Dry Chemical | 32120 | 300 lb. (136 kg) | 30-A:320-B:C | 53 sec | 30-40 ft. (9.1-12.2 m) | 810 lb. (368 kg) |
| A-350-RG | ABC Dry Chemical | 32140 | 300 lb. (136 kg) | 30-A:320-B:C | 53 sec | 30-40 ft. (9.1-12.2 m) | 810 lb. (368 kg) |
| A-350-PT | ABC Dry Chemical | 32110 | 300 lb. (136 kg) | 30-A:320-B:C | 57 sec | 30-40 ft. (9.1-12.2 m) | 700 lb. (318 kg) |
| A-350-PT | ABC Dry Chemical | 32130 | 300 lb. (136 kg) | 30-A:320-B:C | 57 sec | 30-40 ft. (9.1-12.2 m) | 700 lb. (318 kg) |
| S-150-RG | Standard Dry Chemical | 31220 | 150 lb. (68 kg) | 240-B:C | 48 sec | 30-40 ft. (9.1-12.2 m) | 438 lb. (199 kg) |
| S-150-RG | Standard Dry Chemical | 31240 | 150 lb. (68 kg) | 240-B:C | 48 sec | 30-40 ft. (9.1-12.2 m) | 473 lb. (215 kg) |
| S-150-RG | Standard Dry Chemical | 31250 | 150 lb. (68 kg) | 240-B:C | 48 sec | 30-40 ft. (9.1-12.2 m) | 473 lb. (215 kg) |
| S-150-PT | Standard Dry Chemical | 31250 | 150 lb. (68 kg) | 240-B:C | 43 sec | 30-40 ft. (9.1-12.2 m) | 370 lb. (168 kg) |
| S-350-RG | Standard Dry Chemical | 32220 | 350 lb. (159 kg) | 320-B:C | 59 sec | 30-40 ft. (9.1-12.2 m) | 860 lb. (391 kg) |
| S-350-RG | Standard Dry Chemical | 32240 | 350 lb. (159 kg) | 320-B:C | 59 sec | 30-40 ft. (9.1-12.2 m) | 860 lb. (391 kg) |
| S-350-PT | Standard Dry Chemical | 32210 | 350 lb. (159 kg) | 320-B:C | 50 sec | 30-40 ft. (9.1-12.2 m) | 750 lb. (341 kg) |
| S-350-PT | Standard Dry Chemical | 32230 | 350 lb. (159 kg) | 320-B:C | 50 sec | 30-40 ft. (9.1-12.2 m) | 750 lb. (341 kg) |
| K-50-SP | Purple K Dry Chemical | 30030 | 50 lb. (22.7 kg) | 160-B:C | 34 sec | 25-35 ft. (7.6-10.7 m) | 193 lb. (88 kg) |
| K-150-SP | Purple K Dry Chemical | 30310 | 125 lb. (56.7 kg) | 320-B:C | 54 sec | 30-40 ft. (9.1-12.2 m) | 343 lb. (156 kg) |
| K-150-RG | Purple K Dry Chemical | 31320 | 125 lb. (56.7 kg) | 320-B:C | 57 sec | 30-40 ft. (9.1-12.2 m) | 413 lb. (188 kg) |
| K-150-RG | Purple K Dry Chemical | 31340 | 125 lb. (56.7 kg) | 320-B:C | 57 sec | 30-40 ft. (9.1-12.2 m) | 448 lb. (204 kg) |
| K-150-RG | Purple K Dry Chemical | 31350 | 125 lb. (56.7 kg) | 320-B:C | 57 sec | 30-40 ft. (9.1-12.2 m) | 448 lb. (204 kg) |
| K-150-PT | Purple K Dry Chemical | 31310 | 125 lb. (56.7 kg) | 320-B:C | 54 sec | 30-40 ft. (9.1-12.2 m) | 345 lb. (147 kg) |
| K-350-RG | Purple K Dry Chemical | 32320 | 300 lb. (136 kg) | 320-B:C | 56 sec | 30-40 ft. (9.1-12.2 m) | 810 lb. (368 kg) |
| K-350-RG | Purple K Dry Chemical | 32340 | 300 lb. (136 kg) | 320-B:C | 56 sec | 30-40 ft. (9.1-12.2 m) | 810 lb. (368 kg) |
| K-350-PT | Purple K Dry Chemical | 32310 | 300 lb. (136 kg) | 320-B:C | 58 sec | 30-40 ft. (9.1-12.2 m) | 700 lb. (318 kg) |
| K-350-PT | Purple K Dry Chemical | 32330 | 300 lb. (136 kg) | 320-B:C | 58 sec | 30-40 ft. (9.1-12.2 m) | 700 lb. (318 kg) |

US Coast Guard Approved Models - Part numbers 30010, 30110, 30030, 30310 & 31210



| UNIT HEIGHT | UNIT WIDTH | UNIT DEPTH | HOSE LENGTH & DIAMETER | WHEEL TYPE | WHEEL DIAMETER |
|--------------------|---------------------|---------------------|------------------------------------|-------------------------|---------------------------------------|
| 47 inches (119 cm) | 24 inches (61 cm) | 26.5 inches (67 cm) | 25 ft. x .50 in. (7.6 m x 1.3 cm) | Rubber | 12.3 in. x 3.5 in. (31.3 cm x 8.9 cm) |
| 51 inches (128 cm) | 26 inches (66 cm) | 38 inches (96.5 cm) | 50 ft. x .75 in. (15.2 m x 1.9 cm) | Rubber | 16 in. x 4 in. (40.6 cm x 10.2 cm) |
| 50 inches (127 cm) | 24 inches (61 cm) | 42 inches (105 cm) | 50 ft. x .75 in. (15.2 m x 1.9 cm) | Rubber | 16 in. x 4 in. (40.6 cm x 10.2 cm) |
| 55 inches (139 cm) | 32 inches (81.3 cm) | 46 inches (117 cm) | 50 ft. x .75 in. (15.2 m x 1.9 cm) | Steel | 36 in. x 2.5 in. (91.4 cm x 6.4 cm) |
| 55 inches (139 cm) | 32 inches (81.3 cm) | 46 inches (117 cm) | 50 ft. x .75 in. (15.2 m x 1.9 cm) | Steel with rubber tread | 36 in. x 2.5 in. (91.4 cm x 6.4 cm) |
| 50 inches (127 cm) | 24 inches (61 cm) | 42 inches (105 cm) | 50 ft. x .75 in. (15.2 m x 1.9 cm) | Rubber | 16 in. x 4 in. (40.6 cm x 10.2 cm) |
| 58 inches (147 cm) | 36 inches (91.4 cm) | 48 inches (122 cm) | 50 ft. x 1 in. (15.2 m x 2.5 cm) | Steel | 36 in. x 6 in. (91.4 cm x 15.2 cm) |
| 58 inches (147 cm) | 36 inches (91.4 cm) | 48 inches (122 cm) | 50 ft. x 1 in. (15.2 m x 2.5 cm) | Steel with rubber tread | 36 in. x 6 in. (91.4 cm x 15.2 cm) |
| 57 inches (147 cm) | 36 inches (91.4 cm) | 48 inches (122 cm) | 50 ft. x 1 in. (15.2 m x 2.5 cm) | Steel | 36 in. x 6 in. (91.4 cm x 15.2 cm) |
| 57 inches (147 cm) | 36 inches (91.4 cm) | 48 inches (122 cm) | 50 ft. x 1 in. (15.2 m x 2.5 cm) | Steel with rubber tread | 36 in. x 6 in. (91.4 cm x 15.2 cm) |
| 50 inches (127 cm) | 24 inches (61 cm) | 42 inches (105 cm) | 50 ft. x .75 in. (15.2 m x 1.9 cm) | Rubber | 16.4 in. x 4 in. (40.6 cm x 10.2 cm) |
| 55 inches (139 cm) | 32 inches (81.3 cm) | 46 inches (117 cm) | 50 ft. x .75 in. (15.2 m x 1.9 cm) | Steel | 36 in. x 2.5 in. (91.4 cm x 6.4 cm) |
| 55 inches (139 cm) | 32 inches (81.3 cm) | 46 inches (117 cm) | 50 ft. x .75 in. (15.2 m x 1.9 cm) | Steel with rubber tread | 36 in. x 2.5 in. (91.4 cm x 6.4 cm) |
| 50 inches (127 cm) | 24 inches (61 cm) | 42 inches (105 cm) | 50 ft. x .75 in. (15.2 m x 1.9 cm) | Rubber | 16 in. x 4 in. (40.6 cm x 10.2 cm) |
| 58 inches (147 cm) | 36 inches (91.4 cm) | 48 inches (122 cm) | 50 ft. x 1 in. (15.2 m x 2.5 cm) | Steel | 36 in. x 6 in. (91.4 cm x 15.2 cm) |
| 58 inches (147 cm) | 36 inches (91.4 cm) | 48 inches (122 cm) | 50 ft. x 1 in. (15.2 m x 2.5 cm) | Steel with rubber tread | 36 in. x 6 in. (91.4 cm x 15.2 cm) |
| 58 inches (147 cm) | 36 inches (91.4 cm) | 48 inches (122 cm) | 50 ft. x 1 in. (15.2 m x 2.5 cm) | Steel | 36 in. x 6 in. (91.4 cm x 15.2 cm) |
| 58 inches (147 cm) | 36 inches (91.4 cm) | 48 inches (122 cm) | 50 ft. x 1 in. (15.2 m x 2.5 cm) | Steel with rubber tread | 36 in. x 6 in. (91.4 cm x 15.2 cm) |
| 47 inches (119 cm) | 24 inches (61 cm) | 26.5 inches (67 cm) | 25 ft. x .50 in. (7.6 m x 1.3 cm) | Rubber | 12.3 in. x 3.5 in. (31.3 cm x 8.9 cm) |
| 51 inches (128 cm) | 26 inches (66 cm) | 38 inches (96.5 cm) | 50 ft. x .75 in. (15.2 m x 1.9 cm) | Rubber | 16 in. x 4 in. (40.6 cm x 10.2 cm) |
| 50 inches (127 cm) | 24 inches (61 cm) | 42 inches (105 cm) | 50 ft. x .75 in. (15.2 m x 1.9 cm) | Rubber | 16 in. x 4 in. (40.6 cm x 10.2 cm) |
| 55 inches (139 cm) | 32 inches (81.3 cm) | 46 inches (117 cm) | 50 ft. x .75 in. (15.2 m x 1.9 cm) | Steel | 36 in. x 2.5 in. (91.4 cm x 6.4 cm) |
| 55 inches (139 cm) | 32 inches (81.3 cm) | 46 inches (117 cm) | 50 ft. x .75 in. (15.2 m x 1.9 cm) | Steel with rubber tread | 36 in. x 2.5 in. (91.4 cm x 6.4 cm) |
| 50 inches (127 cm) | 24 inches (61 cm) | 42 inches (105 cm) | 50 ft. x .75 in. (15.2 m x 1.9 cm) | Rubber | 16 in. x 4 in. (40.6 cm x 10.2 cm) |
| 58 inches (147 cm) | 36 inches (91.4 cm) | 48 inches (122 cm) | 50 ft. x 1 in. (15.2 m x 2.5 cm) | Steel | 36 in. x 6 in. (91.4 cm x 15.2 cm) |
| 58 inches (147 cm) | 36 inches (91.4 cm) | 48 inches (122 cm) | 50 ft. x 1 in. (15.2 m x 2.5 cm) | Steel with rubber tread | 36 in. x 6 in. (91.4 cm x 15.2 cm) |
| 58 inches (147 cm) | 36 inches (91.4 cm) | 48 inches (122 cm) | 50 ft. x 1 in. (15.2 m x 2.5 cm) | Steel | 36 in. x 6 in. (91.4 cm x 15.2 cm) |
| 58 inches (147 cm) | 36 inches (91.4 cm) | 48 inches (122 cm) | 50 ft. x 1 in. (15.2 m x 2.5 cm) | Steel with rubber tread | 36 in. x 6 in. (91.4 cm x 15.2 cm) |



For more information please contact:

**Buckeye Fire Equipment
PO Box 428
110 Kings Road
Kings Mountain
North Carolina 28086**

**Tel. 704 739 7415
Fax. 704 739 7418
www.buckeyef.com**