

# 1 1/2" ProVenger FG Fire Hose Nozzle with pistol grip

### **STYLE 4116**

The 1 1/2" ProVenger FG is the fixed gallonage style for the ProVenger Series Nozzles. ProVenger nozzles provide great stream quality and a simple design to give you the value you expect from Akron Brass.

Find an Akron Brass distributor near you for more information about this fire hose nozzle.

### Features

- Great stream performance
- Simplified nozzle training
- Affordably priced
- Standard swivel inlet 1 1/2" NH (38 mm), additional inlet types available
- · Easy to operate
- 150 gpm (550 lpm) @ 75 or 100 psi (5 or 7 bar)
- Raised lug marks straight stream for limited visibility operations
- Quick change pattern adjustment

### **Applications/Solutions**

- Fire OEMs
- Firefighting Airport (ARFF)
- Firefighting Industrial
- Firefighting Structural
- Firefighting Wildland Forestry



### Specifications

•	
Style	4116
Certification(s)	NFPA 1964 COMPLANT
	CE
Warranty	WARRANTY
Weight	4.3 lbs (2 kg)
Material	Pyrolite
Brand	ProVenger
Swivel Inlet	Standard 1 1/2" or 2 1/2" NH, additional inlet types available (38 mm, 65 mm)
Length	11" (280 mm)
Height	9 -1/8" (232 mm)
Flow (GPM)	150 GPM

1.800.228.1161 | akronbrass.com | akroncare@idexcorp.com

Copyright 2020 Akron Brass Company. All rights reserved. No portion of this can be reproduced without the express written consent of the Akron Brass Company. (06/20)

Flow (LPM)	550 LPM
Orifice Optional	Fixed Orifice

## 1 1/2" ProVenger FG Fire Hose Nozzle with pistol grip

### **STYLE 4116**

### Style 4116 (Fixed gallonage)

Lightweight fog and straight stream nozzle with fixed constant gallonage settings labeled on the baffle head. Nozzle shall have spinning turbine teeth, multiple pattern detents, a one-piece solid nylon reinforced bumper, one-piece solid rubber-like handle with dual stops, dual drive trunnions, and an extruded single piece Pyrolite body. The nozzle also shall have a minimum 100° fog pattern, a fulltime swivel inlet, be capable of flushing without shutting down, and a 5 year warranty. Must meet all aspects of NFPA 1964 with test results available.