


## Beach Bouncer Description



Beach Bouncer is a seaweed control barrier that consists of a heavy duty coated mesh fabric skirt supported by a flotation encased in vinyl coated fabric. It features a stainless steel load carrying cable above & below the flotation and a heavy galvanized chain ballast at the bottom of the skirt.





1309 West Main, Carmi, IL 62821, USA  
Tel: +1 (618) 382 2525 Fax: +1 (618) 382 3610  
E-mail: [elastec@elastec.com](mailto:elastec@elastec.com)  
Web Page: [www.elastec.com](http://www.elastec.com)

Section Length: 100 ft (30 m)  
Skirt Depth: 3 ft (0.9 m)  
Freeboard: 12 inches (0.3 m)  
Boom Fabric: 22 oz PVC in Royal Blue (other colors available)  
500 lb/square inch tensile strength  
Skirt Fabric: 18 oz WOVEN PVC in Black  
30% open area (1/8 inch / 3.17 mm) opening size mesh  
Tension Cable: 5/16 inch stainless steel cable with a break strength of 10,540 lb is sheathed in vinyl and seamed into the fabric above and under the flotation. This cable is shackled to the section connectors for uniform tension load transfer.  
Ballast: ½ inch (or heavier) galvanized steel chain enclosed in a double layer fabric pocket at the bottom of the skirt. The ballast chain enables the skirt to hang vertically in the water column preventing the seagrass from migrating under or billowing the skirt.  
Section Connector: Marine grade aluminum Universeal Connectors  
Below the connector, skirts are joined by rope ties between evenly spaced grommets on the skirts. The ballast chains connect via stainless steel shackles.  
Anchor Points: Provided every 25 ft (7.6 m)  
Optional: Marker buoys, anchor systems, navigational warning lights, repair kits

BBC-031  
4/15/16