



# LINGJACK

## 林傑

### 135LTR FOAM CARTRIDGE OPERATED MOBILE FIRE EXTINGUISHER

MODEL : C-135FTC

#### Specification :

- Capacity : 135 Litre
- Extinguishing Medium : Foam
- Propellant Type : 3kg CO<sub>2</sub>
- Discharge Time : 175 sec
- Discharge Range : 10 m
- Working Temperature : +5Deg C to +60 Deg C
- Hose Length : 3/4" x 6 meters  
(Optional Up To 12 meter Upon Request)
- Wheel Size : Diameter 406mm x 50mm
- Size : 650 (L) x 710 (D) x 1320(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 205 kg



#### Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Forged Brass Chrome Plated Operating Valve with In-Build Safety Relief
- Solid Rubber Wheel for Easy Maneuverable

**Standards :** Manufactured In Accordance With BS EN 1866-1 : 2007

**Approvals :** LPCB (UK), Wheel Mark (MED), CE Mark (PED), SETSCO (SG)


**Origin :** Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	Class Of Fire	Standard	Approval
20802251	34A,IVB (317B)	A, B	BS EN 1866-1:2007	LPCB, MED, CE
20802252	34A,IVB (317B)	A, B	BS EN 1866-1:2007	SETSCO



EN3-7:2004 + A1:2007  
Cert No. 501a



0832



0832



SETSCO

**GOOD QUALITY GREAT SERVICES**

[www.lingjack.com](http://www.lingjack.com)

Specification subjects to change without prior notice (0620 R01)