

SHROPSHIRE SCANIA 4x2 CP31 PUMPING APPLIANCE

Summary

- B type water Tender.
- 3,000 litre water capacity.
- P – Series 4x2 chassis (New Gen Cab).
- 6 person crew cab (Option of 9 Person Cab).



Outline Specification

Chassis Specification

- 4,350mm wheel base
- CP31 crew cab, 4 door steel cab.
- Front & rear air suspension.
- Gross vehicle weight 18,000kg.
- Engine output – Scania DB4x2MNB 280hp Euro 6 emissions .
- Power take off Chelsea top mount PTO (Chelsea 870).
- Tyres – Front and rear 315/70R22.5 .
- Full appliance Data-Logging (Black Box Recorder). In-cab digital status monitor / display panel.

Body Specification

- Emergency One Designed copolymer bodywork.
- Integrated water tank – capacity 3,000 litre.
- Integrated foam tank – capacity 100 litre.
- Stowage to suit customers kit.
- X6 side locker complete with roller shutter doors to customer specification.

Accessories

- Emergency One standard wiring harness installation and canbus control system
- Godiva Prima 2010 pump installation (2000 litres per minute) complete with Round The Pump (RTP) low pressure discharge foam system.
- 24V lighting mast comes with 4 way LED lighting 2x floods 2 spots and handset control . Positioned nearside front of body roof.
- All beams and ladder to customer specification – Nearside beam to carry folding roof ladder and offside beam gantry to carry 9m double extension ladder.
- 13.5m ladder gantry stowed with E1 gantry bracket. 10.5m ladder changeover gantry optional.
- X2 55m hose reels mounted high in middle lockers – hose capacity & position variable.
- Emergency One's ePumpControl & eCabControl
- 4 forward facing breathing apparatus seats complete with storage for masks.

DATA-079/A



Further Options available.
To discuss, please contact Emergency One:

Tel : 01290 424200 / 423815
Fax : 01290 423834

Email : enquiries@emergencyone.co.uk